



## BAL MICROMAX GROUT-EFFECT SEALANT

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 and SI 2020/1577

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

Product Name BAL MICROMAX GROUT-EFFECT SEALANT

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Silicone sealant.

Uses Advised Against Not known.

#### 1.3 Details of the supplier of the safety data sheet

Supplier

Company Identification Building Adhesives Limited

Address Longton Road

Trentham

Stoke on Trent

Postal code

ST4 8JB

Telephone:

+44 (0)1782 591100

Fax

Not known.

E-mail

sdsreply@building-adhesives.com

Office hours

8:30am-5pm, Mon-Fri (excluding bank holidays)

#### 1.4 Emergency telephone number

Emergency Phone No. 01865 407 333 (24/7 all year)

Contact No information available.

National response centre

Address

NHS Direct

Emergency Phone No.

+44 111

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567 Not classified as dangerous for supply/use.

#### 2.2 Label elements

According to GB CLP Regulations, UK SI 2019/720 and UK SI 2020/1567

Product Name

BAL MICROMAX GROUT-EFFECT SEALANT

Hazard Pictogram(s)

None

Signal Word(s)

None

Hazard Statement(s)

EUH208: Contains: 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed. Do not breathe spray or mist. (EUH211 applies only to the white version).

Active biocide used to treat the article: 2-octyl-2H-isothiazol-3-one.



## BAL MICROMAX GROUT-EFFECT SEALANT

### 2.3 Other hazards

No data available.

### 2.4 Additional Information

For full text of H/P Statements see section 16.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 Substances

Not applicable.

### 3.2 Mixtures

HAZARDOUS INGREDIENT(S)	CAS No.	EC No. / Registration number(s)	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
Amorphous silica	112945-52-5	601-216-3	5-10	Not classified	None
Triacetoxyethylsilane	17689-77-9	241-677-4	<5	Skin Corr. 1B H314	GHS05
Octamethylcyclotetrasiloxane	556-67-2	209-136-7	<0.1	Repr. 2 H361f Aquatic Chronic 1 H410	GHS08 GHS09
2-Octyl-2H-isothiazol-3-one	26530-20-1	247-761-7	<0.1	Acute Tox. 3 H301 Acute Tox. 3 H311 Skin Corr. 1B H314 Skin Sens. 1A H317 Eye Dam. 1 H318 Acute Tox. 2 H330 Aquatic Acute 1 H400 Aquatic Chronic 1 H410	GHS06 GHS05 GHS07 GHS09

For full text of H/P Statements see section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

Inhalation	Treat symptomatically. Remove patient to fresh air.
Skin Contact	Take off immediately all contaminated clothing and wash it before reuse. Remove with a cloth or paper. Wash off immediately with soap and water. If skin irritation occurs: Get medical advice/attention. Specific treatment (see Medical Advice on this label).
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Seek medical advice immediately. Never give anything by mouth to an unconscious person. Get medical attention immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

May cause irritation. Allergic contact dermatitis.



## BAL MICROMAX GROUT-EFFECT SEALANT

### 4.3 Indication of any immediate medical attention and special treatment needed

Specific treatment (see Medical Advice on this label). Treat symptomatically.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media

Suitable Extinguishing media As appropriate for surrounding fire.

Unsuitable extinguishing media None.

### 5.2 Special hazards arising from the substance or mixture

May decompose in a fire, giving off toxic and irritant vapours.

### 5.3 Advice for firefighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Dike fire control water for later disposal.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Wear suitable protective clothing, gloves and eye/face protection.

### 6.2 Environmental precautions

Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.

### 6.3 Methods and material for containment and cleaning up

Absorb spillages onto sand, earth or any suitable adsorbent material. Contain spillages with sand, earth or any suitable adsorbent material. Earth may be shovelled to contain spillage and to avoid contamination of sewers and watercourses.

### 6.4 Reference to other sections

See also section 8, 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid breathing vapours/spray. Wash hands and exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

### 7.2 Conditions for safe storage, including any incompatibilities

Storage temperature

Ambient.

Storage life

Stable under normal conditions.

Incompatible materials

Acids; alkalis; Alcohols.

### 7.3 Specific end use(s)

See 1.2.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

8.1.1 Occupational Exposure Limits

No Occupational Exposure Limit assigned.



## BAL MICROMAX GROUT-EFFECT SEALANT

### 8.2 Exposure controls

8.2.1. Appropriate engineering controls Ensure adequate ventilation. A washing facility/water for eye and skin cleaning purposes should be present.

8.2.2. Personal protection equipment



Eye Protection Wear eye protection with side protection (EN166).



Skin protection Wear protective clothing and gloves: Impervious gloves (EN 374).



Respiratory protection Normally no personal respiratory protection is necessary.



Thermal hazards None known.

8.2.3. Environmental Exposure Controls Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	Liquid. Paste Colour : Various.
Odour	Acetic acid.
Odour threshold	Not known.
pH	Not known.
Melting point/freezing point	Not known.
Initial boiling point and boiling range	Not known.
Flash Point	Not known.
Evaporation rate	Not known.
Flammability (solid, gas)	Not known.
Upper/lower flammability or explosive limits	Not known.
Vapour pressure	Not known.
Vapour density	Not known.
Density (g/ml)	1.03.
Relative density	Not known.
Solubility(ies)	Solubility (Water) : Insoluble. Solubility (Other) : Not known.
Partition coefficient: n-octanol/water	Not known.
Auto-ignition temperature	Not known.
Decomposition Temperature (°C)	Not known.



## BAL MICROMAX GROUT-EFFECT SEALANT

Viscosity Not known.  
Explosive properties Not known.  
Oxidising properties Not known.

### 9.2 Other information

None.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

None anticipated.

### 10.2 Chemical Stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

### 10.4 Conditions to avoid

None anticipated.

### 10.5 Incompatible materials

Not known.

### 10.6 Hazardous decomposition products

No hazardous decomposition products known.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

Acute toxicity - Ingestion Calculation method : Not classified.  
Calculation method : Calculated acute toxicity estimate (ATE) Calc  
ATE - 55190.07

Acute toxicity - Skin Contact Calculation method : Not classified.  
Calculation method : Calculated acute toxicity estimate (ATE) Calc  
ATE - 20872484

Acute toxicity - Inhalation Calculation method : Not classified.  
Calculation method : Calculated acute toxicity estimate (ATE) Calc  
ATE - 33557.05

Skin corrosion/irritation Calculation method : Not classified.  
Serious eye damage/irritation Calculation method : Not classified.  
Skin sensitization data Calculation method : Not classified.  
Respiratory sensitization data Calculation method : Not classified.  
Germ cell mutagenicity Calculation method : Not classified.  
Carcinogenicity Calculation method : Not classified.  
Reproductive toxicity Calculation method : Not classified.  
Lactation Calculation method : Not classified.  
STOT - single exposure Calculation method : Not classified.  
STOT - repeated exposure Calculation method : Not classified.  
Aspiration hazard Calculation method : Not classified.

### 11.2 Other information

Endocrine disrupting properties: List II: Substances under evaluation for endocrine disruption under an EU legislation 556-67-2 (Human health) ; List III: Substances considered, by the evaluating National Authority, to have endocrine disrupting properties 556-67-2 (Human health)



## BAL MICROMAX GROUT-EFFECT SEALANT

### SECTION 12: ECOLOGICAL INFORMATION

#### 12.1 Toxicity

Toxicity - Aquatic invertebrates Low toxicity to invertebrates.

Toxicity - Fish Low toxicity to fish.

Toxicity - Algae Low toxicity to algae.

Toxicity - Sediment Not classified.

Compartment

Toxicity - Terrestrial Not classified.

Compartment

#### 12.2 Persistence and degradability

Not known.

#### 12.3 Bioaccumulative potential

Not known.

#### 12.4 Mobility in soil

Not known.

#### 12.5 Results of PBT and vPvB assessment

Not known.

#### 12.6 Other adverse effects

None known.

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods

Dispose of contents in accordance with local, state or national legislation. Send to a licensed recycler, reclaimer or incinerator. Dispose of this material and its container to hazardous or special waste collection point. Dispose at suitable refuse site.

#### 13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

### SECTION 14: TRANSPORT INFORMATION

**Not classified as hazardous for transport.**

#### 14.1 UN number

Not applicable

#### 14.2 UN proper shipping name

Not applicable

#### 14.3 Transport hazard class(es)

Not applicable

#### 14.4 Packing group

Not applicable

#### 14.5 Environmental hazards

Not classified as a Marine Pollutant.

#### 14.6 Special precautions for user

Not known

#### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not known



## BAL MICROMAX GROUT-EFFECT SEALANT

### SECTION 15: REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

United Kingdom Regulations - Authorisations and/or Restrictions On Use

UK REACH Candidate List of octamethylcyclotetrasiloxane (556-67-2)

Substances of Very High Concern

for Authorisation

UK REACH Authorisation List Not listed

(Annex XIV) list of substances

subject to authorisation

UK REACH Restrictions List octamethylcyclotetrasiloxane (556-67-2), Triacetoxyethylsilane

(Annex XVII) Restrictions on the (17689-77-9), octhiline (ISO)octhiline (ISO); 2-octyl-2H-

manufacture, placing on the isothiazol-3-one; [OIT] (26530-20-1)

market and use of certain

dangerous substances, mixtures

and articles

UK REACH Rolling Action Plan Not listed

(RAP)

The Persistent Organic Pollutants Not listed

Regulations 2007 (SI 2007/3106)

as amended

The Ozone-Depleting Substances Not listed

and Fluorinated Greenhouse

Gases (Amendment etc.) (EU

Exit) Regulations 2019 (SI

2019/583)

The Prior Informed Consent (PIC) Not listed

Regulations concerning the

export and import of hazardous

chemicals SI2008/2108 as

amended

European Regulations - Authorisations and/or Restrictions On Use

Community Rolling Action Plan Not listed

(CoRAP)

#### 15.2 Chemical Safety Assessment

United Kingdom A REACH chemical safety assessment has not been carried out.

### SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements:

#### LEGEND

Hazard Pictogram(s) None.



## BAL MICROMAX GROUT-EFFECT SEALANT

GHS05: GHS: Corrosion  
 GHS06: GHS: Skull and crossbones  
 GHS07: GHS: Exclamation mark  
 GHS08: GHS: Health hazard  
 GHS09: GHS: Environment

### Hazard classification

Acute Tox. 3 : Acute toxicity, Category 3  
 Acute Tox. 4 : Acute toxicity, Category 4  
 Acute Tox. 3 : Acute toxicity, Category 3  
 Skin Corr. 1 : Skin corrosion/irritation, Category 1  
 Skin Corr. 1B : Skin corrosion/irritation, Category 1B  
 Skin Sens. 1A : Skin sensitization, Category 1A  
 Eye Dam. 1 : Serious eye damage/irritation, Category 1  
 Acute Tox. 2 : Acute toxicity, Category 2  
 Repr. 2 : Reproductive toxicity, Category 2  
 Aquatic Acute 1 : Hazardous to the aquatic environment, Acute, Category 1  
 Aquatic Chronic 1 : Hazardous to the aquatic environment, Chronic, Category 1

### Hazard Statement(s)

H301: Toxic if swallowed.  
 H302: Harmful if swallowed.  
 H311: Toxic in contact with skin.  
 H314: Causes severe skin burns and eye damage.  
 H317: May cause an allergic skin reaction.  
 H318: Causes serious eye damage.  
 H330: Fatal if inhaled.  
 H361f: Suspected of damaging fertility.  
 H400: Very toxic to aquatic life.  
 H410: Very toxic to aquatic life with long lasting effects.

### Precautionary Statement(s)

None.

### Acronyms

ATE : Acute Toxicity Estimate  
 CAS : Chemical Abstracts Service  
 DNEL : Derived No Effect Level





## BAL MICROMAX GROUT-EFFECT SEALANT

EC : European Community  
 EINECS : European Inventory of Existing Commercial Chemical Substances  
 LTEL : Long term exposure limit  
 PBT : Persistent, Bioaccumulative and Toxic  
 PNEC : Predicted No Effect Concentration  
 REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals  
 STEL : Short term exposure limit  
 STOT : Specific Target Organ Toxicity  
 vPvB : very Persistent and very Bioaccumulative

Key literature references and sources for data used to compile the SDS  
 GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567

Training Advice  
 Regular safety training as appropriate.

Issued by: Head of R+D  
 Issue number: 01

Key literature references and sources for data used to compile the SDS  
 GB CLP Regulation, UK SI 2019/720 and UK SI 2020/1567

**Disclaimers**  
 Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. BUILDING ADHESIVES LTD gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. BUILDING ADHESIVES LTD accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.