

2 Port Zone Valve

2 port motorised zone valve for heating and hot water applications.

Overview

Reliance Vales 2 Port Zone Valves are designed for use in heating systems to isolate zones or equipment when the motor within the zone valve is de-energised. The valve can shut off water flow or control and regulate water flow through domestic and light commercial central heating systems.

Designed with an easy to use clip-on detachable head, pre-moulded plug and play cables and a metal manual operating lever, the 2 Port Zone Valve is durable and quick and easy to install to new systems or retrofit to existing systems.

Features & benefits

- Easy to use, clip-on detachable head
- Pre-moulded plug and play cable supplied to connect to motorised head
- Metal manual operating lever for strength and stability
- The motorised head can be retrofitted to other manufacturers' valve body
- Suitable for hot water and central heating use only

Standards & approvals

Electro-Magnetic Compatibility Directive 2004/108/EC

Low Voltage Directive 2006/95/EEC

EC Marking Directive 93/68/EEC

Specifications

Power supply	220-240V, 50/60Hz, 5W
System fuse rating	3A Maximum
Auxiliary switch rating	3A 250VAC
Water temperature	5°C - 88°C
Maximum differential pressure	0.69 bar
Cable length	1m
Maximum pressure	6 bar

Product code	Description	Size
ZONE250305	Two Port Zone Valve	22mm
SKIT250305	Spare actuator head for Reliance Valves 2 Port Zone Valve	22mm



Dimensions – All measurements in mm unless otherwise state

