

INSTARMAC

SAFETY DATA SHEET UltraTileFix ProFlex SP Grey

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name UltraTileFix ProFlex SP Grey

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier Instarmac Group plc
Danny Morson Way
Birch Coppice Business Park
Dordon, Tamworth
Staffordshire. B78 1SE
United Kingdom
Tel: +44 (0) 1827 872244
Fax: +44 (0) 1827 874466
email@instarmac.co.uk www.instarmac.co.uk

1.4. Emergency telephone number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335
Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.

UltraTileFix ProFlex SP Grey

Precautionary statements

P261 Avoid breathing dust.
 P264 Wash contaminated skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/ doctor.
 P312 Call a POISON CENTER/ doctor if you feel unwell.
 P321 Specific treatment (see medical advice on this label).
 P332+P313 If skin irritation occurs: Get medical advice/ attention.
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains PORTLAND CEMENT

Supplementary precautionary statements

P261 Avoid breathing vapour/spray.
 P264 Wash contaminated skin thoroughly after handling.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P312 Call a POISON CENTER/ doctor if you feel unwell.
 P321 Specific treatment (see medical advice on this label).
 P332+P313 If skin irritation occurs: Get medical advice/ attention.
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P362 Take off contaminated clothing.
 P363 Wash contaminated clothing before reuse.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

Classification according to EC 1272/2008 (CLP)

3.2. Mixtures

Quartz	30-60%
CAS number: 14808-60-7	EC number: 238-878-4
Classification	
Not Classified	

UltraTileFix ProFlex SP Grey

PORTLAND CEMENT	10-30%
CAS number: 65997-15-1	
Classification	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
STOT SE 3 - H335	
HIGH ALUMINA CEMENT	10-30%
CAS number: 65997-16-2	EC number: 266-045-5
Classification	
Not Classified	
VINYL ACETATE COPOLYMER	1-5%
CAS number: —	EC number: 925-954-3
Classification	
Not Classified	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If throat irritation or coughing persists, proceed as follows. Get medical attention. Show this Safety Data Sheet to the medical personnel.
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink.
Skin contact	Remove contaminated clothing and rinse skin thoroughly with water. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

7.3. Specific end use(s)

UltraTileFix ProFlex SP Grey

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Quartz

Long-term exposure limit (8-hour TWA): WEL 0.1 mg/m³

PORTLAND CEMENT

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

HIGH ALUMINA CEMENT

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

VINYL ACETATE COPOLYMER

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

10.5. Incompatible materials

10.6. Hazardous decomposition products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

SECTION 12: Ecological Information

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

SECTION 14: Transport information

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

14.6. Special precautions for user

UltraTileFix ProFlex SP Grey

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date	17/01/2018
Hazard statements in full	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation.